

Customer No.: 31561
Application No.: 10/065,343
Docket No.: 9527-US-PA

AMENDMENTS

In The Claims

Claim 1. (currently amended) A power adapter having a freely rotatable direct current (DC) plug connection, comprising:

a main body, including a casing that respectively encloses an adapter circuit board, a DC connector port and an alternating current (AC) connector port, the DC connector port and the AC connector port being respectively arranged on the adapter circuit board;

a DC wire, having a first terminal electrically connected to a DC plug that mates with the DC connector port according to a freely rotatable manner, wherein the DC plug is ~~detachable from~~ detachably snapped to the DC connector port without an aid of using any mechanical tool while the DC plug is prevented from an unintentional separation from the DC connector; and

an AC wire, having a second terminal electrically connected to the AC connector port.

Claim 2. (original) The power adapter of claim 1, wherein the casing further includes an opening at a location corresponding to that of the DC connector port on the adapter circuit board.

Claim 3. (original) The power adapter of claim 2, wherein the DC plug further comprises:

an electrical connecting part, mating with the DC connector port; and

an insulating part, partially covering the electrical connecting part, the insulating part being further provided with a slot that engages by fitting with a rim of the opening of the casing in a manner to allow a free rotation of the DC plug relative to the casing while ensuring the electrical and mechanical connection there between.

Claim 4. (original) The power adapter of claim 3, wherein the insulating part further includes a stress-buffer structure.

Claim 5. (original) The power adapter of claim 1, wherein the casing is formed in an approximately parallelepiped shape.

Customer No.: 31561
Application No.: 10/065,343
Docket No.: 9527-US-PA

Claim 6. (original) The power adapter of claim 1, wherein the casing is formed in an approximately parallelepiped shape and further includes at least a recessed cavity.

Claim 7. (original) The power adapter of claim 6, wherein the DC plug freely and rotatably connects the casing within the recessed cavity.

Claim 8. (original) The power adapter of claim 1, wherein a third terminal of the DC wire further connects an output plug.

Claim 9. (original) The power adapter of claim 1, wherein a fourth terminal of the AC wire connects a plug.

Claim 10. (currently amended) A freely rotatable electrical connection structure of an electrical device, comprising:

an electrical device, having a casing in which is arranged a direct current (DC) connector port and through which is defined an opening; and

an electrical plug, including an electrical connecting part and an insulating part, the electrical connecting part rotatably mating with the DC connector port, and the insulating part further including a slot that engages by fitting with a rim of the opening of the casing in order to secure the connection between the electrical plug and the DC connector port while allowing a free rotation there between;

wherein the DC plug is detachable from detachably snapped to the DC connector port without an aid of using any mechanical tool while the DC plug is prevented from an unintentional separation from the DC connector.

Claim 11. (original) The connection structure of claim 10, wherein the insulating part further includes a stress-buffer structure.

Claim 12. (currently amended) A power adapter having a freely rotatable direct current (DC) plug connection, comprising:

Customer No.: 31561
Application No.: 10/065,343
Docket No.: 9527-US-PA

a main body, including a casing that respectively encloses an adapter circuit board, a DC connector port and an alternating current (AC) connector port, the DC connector port and the AC connector port being respectively arranged on the adapter circuit board;

a DC wire, having a first terminal electrically connected to a DC plug that mates with the DC connector port according to a freely rotatable manner, wherein the DC plug and the DC connector port are separate, and when the DC plug is inserted in detachably snapped to the DC connector port, a rim of an opening of the casing is engaged by fitting with a slot of the DC plug to prevent a-an unintentional separation of the DC plug from the DC connector port while allowing a relative rotation between the DC plug and the DC connector port and a detachment of the DC plug from the DC connector port without an aid of using any mechanical tool; and

an AC wire, having a second terminal electrically connected to the AC connector port.

Claim 13. (previously presented) The power adapter of claim 12, wherein the casing further includes an opening at a location corresponding to that of the DC connector port on the adapter circuit board.

Claim 14. (previously presented) The power adapter of claim 12, wherein the DC plug further comprises:
an electrical connecting part, mating with the DC connector port; and

an insulating part, partially covering the electrical connecting part, the insulating part being further provided with a slot that engages by fitting with a rim of the opening of the casing in a manner to allow a free rotation of the DC plug relative to the casing while ensuring the electrical and mechanical connection there between.

Claim 15. (previously presented) The power adapter of claim 12, wherein the insulating part further includes a stress-buffer structure.

Claim 16. (previously presented) The power adapter of claim 12, wherein the casing is formed in an approximately parallelepiped shape.

Claim 17. (previously presented) The power adapter of claim 12, wherein the casing is formed in an approximately parallelepiped shape and further includes at least a recessed cavity.

Customer No.: 31561
Application No.: 10/065,343
Docket No.: 9527-US-PA

Claim 18. (previously presented) The power adapter of claim 17, wherein the DC plug freely and rotatably connects the casing within the recessed cavity.

Claim 19. (previously presented) The power adapter of claim 12, wherein a third terminal of the DC wire further connects an output plug.

Claim 20. (previously presented) The power adapter of claim 12, wherein a fourth terminal of the AC wire connects a plug.

Claim 21. (currently amended) A freely rotatable electrical connection structure of an electrical device, comprising:

an electrical device, having a casing in which is arranged a direct current (DC) connector port and through which is defined an opening; and

an electrical plug, including an electrical connecting part and an insulating part, the electrical connecting part rotatably mating with the DC connector port, and the insulating part further including a slot that engages by fitting with a rim of the opening of the casing in order to secure the connection between the electrical plug and the DC connector port while allowing a free rotation there between;

wherein the electrical plug and the DC connector port are separate, and when the electrical plug is inserted ~~is detachably snapped to~~ the DC connector port, the rim of an opening of the casing is engaged by fitting with the slot of the electrical plug to prevent ~~a-an unintentional~~ separation of the electrical plug from the DC connector port while allowing a relative rotation between the electrical plug and the DC connector port and a detachment of the DC plug from the DC connector port without an aid of using any mechanical tool.

Claim 22. (previously presented) The connection structure of claim 21, wherein the insulating part further includes a stress-buffer structure.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.